

## Safety data sheet according to U.S.A. Federal Hazcom 2012

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name **MASTER LEATHER CARE HAND RUB SEALER**  
**UNITERS HAND RUB SEALER**

1.2. Relevant identified uses of the substance or mixture and uses advised against  
Intended use **Protective cream for leathers.**

#### 1.3. Details of the supplier of the safety data sheet

Name **Uniters Spa**  
Full address **Via E. De Nicola, 1**  
District and Country **36075 Montecchio Maggiore (VI)**  
**Italia**  
**Tel. 0039 0444 499099**  
**Fax 0039 0444 499106**

e-mail address of the competent person  
responsible for the Safety Data Sheet **safetydata@uniters.com**

#### 1.4. Emergency telephone number

For urgent inquiries refer to **Poison Center**  
**:Albuquerque,Amarillo,Atlanta,Baltimore,Birmingham,Boston,Buffalo,Charleston,Charlotte,Charlottesville,Chicago,Cincinnati,Cleveland,Columbia,Columbus,Dallas,Davis,Denver,Detroit,El Paso,Farmington,Galveston,Harrisbury,Indianapolis,Jackson,Jacksonville,Kansas City, Little Rock, Long Island,Louisville,Madera,Miami,Milwaukee,Minneapolis,Nashville,New York,Newark,Oklahoma City,Omaha,Philadelphia,Phoenix,Pittsburgh,Portland,Richmond,Rochester,Salt Lake City,San Antonio,San Diego,San Francisco,Seattle,Shreveport,Sioux City,St. Louis,Syracuse,Tampa, Temple,Tucson,Tuscaloosa,Washington DC : 18002221222**

### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is not --  
classified as hazardous  
pursuant to the provisions  
set forth in OSHA Hazard  
Communication Standard  
(HCS) (29 CFR  
1910.1200). However,  
since the product  
contains hazardous  
substances in  
concentrations such as to  
be declared in section no.  
3, it requires a safety data  
sheet with appropriate  
information.

Signal words: --

**MASTER LEATHER CARE HAND RUB SEALER**

Hazard statements:

--

Precautionary statements:

Prevention:

--

Response:

--

Storage:

--

Disposal:

--

2.2. Other hazards.

The product is not classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

**SECTION 3. Composition/information on ingredients.****3.1. Substances.**

Information not relevant.

**3.2. Mixtures.**

Contains:

Identification.	Conc. %.	Classification:
<b>DIPROPYLENE GLYCOL MONOMETHYL ETHER</b>		
CAS. 34590-94-8	4 - 4.5	
<b>2-(2-BUTOXYETHOXY)ETHANOL</b>		
CAS. 112-34-5	0.6 - 0.7	Eye irritation, category 2 H319
<b>Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides</b>		
CAS. 68424-85-1	0.1 - 0.15	Acute toxicity, category 4 H302, Acute toxicity, category 4 H312, Skin corrosion, category 1B H314, Hazardous to the aquatic environment, acute toxicity, category 1 H400

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures.****4.1. Description of first aid measures.**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical

**MASTER LEATHER CARE HAND RUB SEALER**

advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

**4.2. Most important symptoms and effects, both acute and delayed.**

For symptoms and effects caused by the contained substances, see chap. 11.

**4.3. Indication of any immediate medical attention and special treatment needed.**

Information not available.

**SECTION 5. Firefighting measures.****5.1. Extinguishing media.****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

**5.2. Special hazards arising from the substance or mixture.****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

**5.3. Advice for firefighters.****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures.****6.1. Personal precautions, protective equipment and emergency procedures.**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**MASTER LEATHER CARE HAND RUB SEALER****6.2. Environmental precautions.**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up.**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections.**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage.****7.1. Precautions for safe handling.**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

**7.2. Conditions for safe storage, including any incompatibilities.**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s).**

Information not available.

**SECTION 8. Exposure controls/personal protection.****8.1. Control parameters.**

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC;
	TLV-ACGIH	Directive 2000/39/EC. ACGIH 2014

**MASTER LEATHER CARE HAND RUB SEALER****DIPROPYLENE GLYCOL MONOMETHYL ETHER****Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	606	100	909	150	SKIN.
OEL	EU	308	50			SKIN.
OSHA	USA	600	100			SKIN.
CAL/OSHA	USA	600	100	900	150	SKIN.
NIOSH	USA	600	100	900	150	SKIN.

**2-(2-BUTOXYETHOXY)ETHANOL****Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	67.5	10	101.2	15	
TLV-ACGIH	-	66	10			

**8.2. Exposure controls.**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

**HAND PROTECTION**

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

**EYE PROTECTION**

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

**ENVIRONMENTAL EXPOSURE CONTROLS.**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties.****9.1. Information on basic physical and chemical properties.**

**MASTER LEATHER CARE HAND RUB SEALER**

Appearance	dense liquid
Colour	whitish
Odour	perfumed
Odour threshold.	Not available.
pH.	3.5-5.5
Melting point / freezing point.	Not available.
Initial boiling point.	> 100 °C.
Boiling range.	Not available.
Flash point.	> 90 °C.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	Not available.
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

**9.2. Other information.**

Solid content. 0,03 %

**SECTION 10. Stability and reactivity.****10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM: can form flammable mixtures with the air.

**10.2. Chemical stability.**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions.**

No hazardous reactions are foreseeable in normal conditions of use and storage.

**10.4. Conditions to avoid.**

None in particular. However the usual precautions used for chemical products should be respected.

**10.5. Incompatible materials.**

**MASTER LEATHER CARE HAND RUB SEALER**

Information not available.

**10.6. Hazardous decomposition products.**

Information not available.

**SECTION 11. Toxicological information.****11.1. Information on toxicological effects.**

2-(2-BUTOXYETHOXY)ETHANOL: can be absorbed by inhalation, ingestion and skin contact; it is irritant to the skin and especially to the eyes; spleen damage may occur. Inhalation is unlikely to occur at room temperature due to the low vapour tension of the substance.

2-(2-BUTOXYETHOXY)ETHANOL  
LD50 (Oral).3384 mg/kg Rat  
LD50 (Dermal).2700 mg/kg Rabbit

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides  
LD50 (Oral).398 mg/kg Ratto  
LD50 (Dermal).< 1240 mg/kg Ratto

Carcinogenicity Assessment:91-64-5Coumarin  
IARC:3  
5989-27-5(R)-P-MENTHA-1,8-DIENE  
IARC:3

**SECTION 12. Ecological information.****12.1. Toxicity.**

Information not available.

**12.2. Persistence and degradability.**

DIPROPYLENE GLYCOL  
MONOMETHYL ETHER  
Solubility in water. mg/l 1000 - 10000

Rapidly biodegradable.

**12.3. Bioaccumulative potential.**

DIPROPYLENE GLYCOL  
MONOMETHYL ETHER  
Partition coefficient: n-  
octanol/water. 0.0043

**12.4. Mobility in soil.**

**MASTER LEATHER CARE HAND RUB SEALER**

Information not available.

**12.5. Results of PBT and vPvB assessment.**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects.**

Information not available.

**SECTION 13. Disposal considerations.****13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information.****14.1. UN number.**

Not applicable.

**14.2. UN proper shipping name.**

Not applicable.

**14.3. Transport hazard class(es).**

Not applicable.

**14.4. Packing group.**

Not applicable.

**14.5. Environmental hazards.**



**MASTER LEATHER CARE HAND RUB SEALER**

Not applicable.

**14.6. Special precautions for user.**

Not applicable.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.**

Information not relevant.

**SECTION 15. Regulatory information.****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**U.S. Federal Regulations.Clean Air Act Section 112(b):

34590-94-8

DIPROPYLENE GLYCOL  
MONOMETHYL ETHER (Glycol  
ethers)

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act –  
Priority Pollutants:

No component(s) listed.

Clean Water Act –  
Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

**MASTER LEATHER CARE HAND RUB SEALER**

313 Category Code:

34590-94-8

DIPROPYLENE GLYCOL  
MONOMETHYL ETHER (Glycol  
ethers)

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

34590-94-8

DIPROPYLENE GLYCOL  
MONOMETHYL ETHER (Glycol  
ethers)

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations.

Massachussetts:

8052-41-3

STODDARD SOLVENT

34590-94-8

DIPROPYLENE GLYCOL  
MONOMETHYL ETHER (Glycol  
ethers)

Minnesota:

8052-41-3

STODDARD SOLVENT

34590-94-8

DIPROPYLENE GLYCOL  
MONOMETHYL ETHER (Glycol  
ethers)

57-55-6

1,2-PROPANEDIOL

140-11-4

New Jersey:

8052-41-3

STODDARD SOLVENT

34590-94-8

DIPROPYLENE GLYCOL  
MONOMETHYL ETHER (Glycol  
ethers)

57-55-6

1,2-PROPANEDIOL

140-11-4

New York:

**MASTER LEATHER CARE HAND RUB SEALER**

No component(s) listed.

Pennsylvania:

8052-41-3	STODDARD SOLVENT
34590-94-8	DIPROPYLENE GLYCOL MONOMETHYL ETHER (Glycol ethers)
57-55-6	1,2-PROPANEDIOL

California:

8052-41-3	STODDARD SOLVENT
34590-94-8	DIPROPYLENE GLYCOL MONOMETHYL ETHER (Glycol ethers)
91-64-5	
97-53-0	
140-11-4	

Proposition 65:

International Regulations.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Canadian WHMIS.

Information not available.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 4</b>	Flammable liquid, category 4
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Skin Corr. 1C</b>	Skin corrosion, category 1C
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>H227</b>	Combustible liquid.
<b>H314</b>	Causes severe skin burns and eye damage.

**MASTER LEATHER CARE HAND RUB SEALER**

<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H400</b>	Very toxic to aquatic life.

**LEGEND:**

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

**GENERAL BIBLIOGRAPHY:**

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

**MASTER LEATHER CARE HAND RUB SEALER**

This document must not be regarded as a guarantee on any specific product property.  
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.  
Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:  
The following sections were modified:  
01 / 02 / 07 / 11 / 14 / 16.