Safety Data Sheet



Issue Date: 21-Aug-2018 Revision Date: 31-Aug-2018 Version 1

1. IDENTIFICATION

Product identifier

Product Name Pro Touch Dark Cherry

Other means of identification

SDS # 69-2102

UN/ID No UN1950

Recommended use of the chemical and restrictions on use

Recommended Use For industrial use.

Details of the supplier of the safety data sheet

Supplier Address Weaver Leather LLC 7540 CR 201 MT Hope, OH 44660

www.weaverleather.com

Emergency telephone number

Company Phone Number Phone: (303) 674-7548

Fax: (303) 674-6859

E-mail: info@weaverleather.com

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Physical state Aerosol

Classification

Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable Aerosols	Category 1
Gases Under Pressure	Compressed Gas

Signal Word

Danger

Revision Date: 31-Aug-2018

Hazard statements

Causes serious eye irritation Suspected of causing cancer

May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



<u>Precautionary Statements - Prevention</u>

Wear eye/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a poison center or doctor/physician if you feel unwell

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Acetone	67-64-1	55-65
Petroleum gases, liquified, sweetened	68476-86-8	25.35
Methoxyisopropyl acetate	108-65-6	1-5
Mineral Spirits	8052-41-3	1-5
Iron(III) oxide	1309-37-1	1-5
Carbon Black	1333-86-4	<1

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret. **

4. FIRST AID MEASURES

Description of first aid measures

General Advice

Get medical advice/attention if you feel unwell.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Revision Date: 31-Aug-2018

Skin Contact Wash off immediately with plenty of water for at least 15 minutes.

Inhalation Remove person to fresh air and keep comfortable for breathing. Call a poison center or

doctor/physician if you feel unwell.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to

organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal PrecautionsUse personal protective equipment as required.

Environmental precautions

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Wear eye/face protection. Wash face, hands and any exposed skin thoroughly after

handling. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from

sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Incompatible Materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not apply	
		to the cellulose acetate fiber	
		industry. It is in effect for all other	
		sectors.	
		(vacated) STEL: 1000 ppm	
Mineral Spirits	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m ³
8052-41-3		TWA: 2900 mg/m ³	Ceiling: 1800 mg/m ³ 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m ³
		(vacated) TWA: 525 mg/m ³	
Iron(III) oxide	TWA: 5 mg/m³ respirable	TWA: 10 mg/m ³ fume	IDLH: 2500 mg/m ³ Fe dust and
1309-37-1	particulate matter	TWA: 15 mg/m³ total dust	fume
			TWA: 5 mg/m ³ Fe dust and fume
		(vacated) TWA: 10 mg/m ³ fume	
		and total dust Iron oxide	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction regulated	
		under Rouge	
Carbon Black	TWA: 3 mg/m³ inhalable	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³
1333-86-4	particulate matter	(vacated) TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³
			TWA: 0.1 mg/m³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Refer to 29 CFR 1910.133 for eye and face protection regulations.

Refer to 29 CFR 1910.138 for appropriate skin and body protection. **Skin and Body Protection**

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Aerosol

Appearance Not determined Odor Not determined Color Not determined **Odor Threshold** Not determined

Property Values Remarks • Method Not determined pН

Melting point / freezing point Not determined Boiling point / boiling range Not determined Flash point Not determined **Evaporation Rate** Not determined Flammability (Solid, Gas) Not determined

Flammability Limit in Air

Upper flammability or explosive Not determined

limits

Lower flammability or explosive Not determined

limits

Vapor Pressure Not determined **Vapor Density** Not determined **Relative Density** Not determined **Water Solubility** Not determined Solubility in other solvents Not determined **Partition Coefficient** Not determined **Autoignition temperature** Not determined **Decomposition temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact Avoid contact with skin.

Inhalation Do not inhale.

Ingestion Do not ingest.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
Methoxyisopropyl acetate 108-65-6	= 8532 mg/kg (Rat)	> 5 g/kg(Rabbit)	-
Iron(III) oxide 1309-37-1	> 10000 mg/kg (Rat)	-	-
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Serious eye damage/eye

irritation

Causes serious eye irritation.

Carcinogenicity Suspected of causing cancer.

Chemical name	ACGIH	IARC	NTP	OSHA
Iron(III) oxide 1309-37-1		Group 3		
Carbon Black 1333-86-4	A3	Group 2B		X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 6,489.23 mg/kg ATEmix (dermal) 15,346.10 mg/kg ATEmix (inhalation-dust/mist) 109.80 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Acetone		8300: 96 h Lepomis macrochirus	10294 - 17704: 48 h Daphnia
67-64-1		mg/L LC50 4.74 - 6.33: 96 h	magna mg/L EC50 Static 12600 -
		Oncorhynchus mykiss mL/L LC50	12700: 48 h Daphnia magna mg/L
		6210 - 8120: 96 h Pimephales	EC50
		promelas mg/L LC50 static	
Methoxyisopropyl acetate		161: 96 h Pimephales promelas	500: 48 h Daphnia magna mg/L
108-65-6		mg/L LC50 static	EC50
Carbon Black		_	5600: 24 h Daphnia magna mg/L
1333-86-4			EC50

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Acetone	-0.24
67-64-1	
Petroleum gases, liquified, sweetened	<=2.8
68476-86-8	
Methoxyisopropyl acetate	0.43
108-65-6	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of WastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

US EPA Waste Number

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Acetone	Ignitable
67-64-1	

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN1950 **UN/ID No Proper Shipping Name** Aerosols Hazard class 2.1

IATA

UN number UN1950

Proper Shipping Name Aerosols, flammable

Transport hazard class(es) 2.1

IMDG

UN number UN1950 **Proper Shipping Name** Aerosols Transport hazard class(es) 2.1

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Acetone	Х	X	X	Χ	Χ	Χ	Х	X
Petroleum gases, liquified, sweetened	Х	Х	Х		Х	Х	Х	Х
Methoxyisopropyl acetate	Х	Х	Х	Х	Х	Χ	Х	Х
Mineral Spirits	Х	Х	Х		Х	Х	Х	Х
Iron(III) oxide	Х	Х	Х	Х	Х	Х	Х	Х
Carbon Black	Х	Х	Х	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Carbon Black - 1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Mineral Spirits 8052-41-3	X	X	X
Iron(III) oxide 1309-37-1	X	X	X
Carbon Black 1333-86-4	X	X	X

16. OTHER INFORMATION

NFPA_	Health Hazards	Flammability	Instability	Special Hazards
	Not determined	Not determined	Not determined	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical hazards	Personal Protection
	Not determined	Not determined	Not determined	Not determined

Issue Date:21-Aug-2018Revision Date:31-Aug-2018Revision Note:New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet