Safety Data Sheet



Issue Date: 01-Aug-2015 Revision Date: 1-Aug-2015 Version 1

1. IDENTIFICATION

Product Identifier

Product Name Weaver Dairy Adhesive, Clear

Other means of identification

SDS # 69-2500

 Product Code
 69-2500

 UN/ID No
 UN1950

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive.

Details of the supplier of the safety data sheet

Supplier Address Weaver Leather LLC 7540 CR 201 MT Hope, OH 44660 www.weaverleather.com

Emergency Telephone Number

Company Phone Number Phone: (303) 674-7548

Fax: (303) 674-6859

E-mail: info@weaverleather.com 1-800-255-3924 (US/Canada)

1-813-248-0585 (International)

2. HAZARDS IDENTIFICATION

Physical state Aerosol Odor Characteristic

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1

Signal Word

Danger

69-2500 - Dairy Adhesive, Clear

Revision Date: 10-May-2016

Hazard statements

Harmful if inhaled

Causes skin irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable aerosol



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do not induce vomiting

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Propane	74-98-6	15-20
n-Butane	106-97-8	8-14
Hexane	110-54-3	65-75
Toluene	108-88-3	3-5

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST-AID MEASURES

First Aid Measures

General Advice If exposed or concerned: Get medical advice/attention.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin Contact Wash with plenty of soap and water. Take off contaminated clothing and wash it before

reuse. If skin irritation occurs: Get medical advice/attention.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Ingestion Immediately call a poison center or doctor/physician. Do not induce vomiting.

Most important symptoms and effects

Symptoms Harmful if inhaled. Causes skin irritation. Suspected of damaging fertility or the unborn

child. May cause drowsiness or dizziness. May cause damage to organs through prolonged

or repeated exposure. May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Extremely flammable aerosol.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal PrecautionsUse personal protective equipment as required.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Obtain special

instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source.

Revision Date: 10-May-2016

Pressurized container: Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from

sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Incompatible Materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Hexane	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	S*	TWA: 1800 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 180 mg/m ³
		(vacated) TWA: 180 mg/m ³	
Toluene	TWA: 20 ppm	TWA: 200 ppm	IDLH: 500 ppm
108-88-3		(vacated) TWA: 100 ppm	TWA: 100 ppm
		(vacated) TWA: 375 mg/m ³	TWA: 375 mg/m ³
		(vacated) STEL: 150 ppm	STEL: 150 ppm
		(vacated) STEL: 560 mg/m ³	STEL: 560 mg/m ³
		Ceiling: 300 ppm	-

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Aerosol

Appearance Not determined Odor Characteristic Color Not determined **Odor Threshold** Not determined

Property Values Remarks • Method

Not determined pН **Melting Point/Freezing Point** Not determined **Boiling Point/Boiling Range** Not determined **Flash Point** Not determined **Evaporation Rate** Not determined Flammability (Solid, Gas) Not determined Flammability Limits in Air **Upper Flammability Limits**

Not determined **Lower Flammability Limit** Not determined **Vapor Pressure** Not determined **Vapor Density** Not determined **Relative Density** Not determined **Water Solubility** Not determined Solubility in other solvents Not determined **Partition Coefficient** Not determined **Auto-ignition Temperature** Not determined **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible Materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact Causes skin irritation.

Inhalation Harmful if inhaled.

Ingestion Do not ingest.

Component Information

Chemical Name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
Hexane	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
110-54-3			
Toluene	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
108-88-3			

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Group 3 IARC components are "not classifiable as human carcinogens".

Chemical Name	ACGIH	IARC	NTP	OSHA
Toluene		Group 3		
108-88-3		•		

Legend

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

Reproductive toxicity Suspected of damaging fertility or the unborn child.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral) 26,531.00 mg/kg
ATEmix (dermal) 12,097.00 mg/kg
ATEmix (inhalation-gas) 14,000.00 mg/L
ATEmix (inhalation-dust/mist) 250.00 mg/L
ATEmix (inhalation-vapor) 718.34 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Hexane 110-54-3		2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through	1000: 24 h Daphnia magna mg/L EC50
Chemical Name	Algae/aquatic plants	Fish	Crustacea
Toluene 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semistatic 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 54: 96 h Oryzias latipes mg/L LC50 static	11.5: 48 h Daphnia magna mg/L EC50 5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Toluene	2.65
108-88-3	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of WastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Toluene	U220	Included in waste streams:		U220
108-88-3		F005, F024, F025, F039,		
		K015, K036, K037, K149,		
		K151		

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Talana	Organic Compounds		Tanda assasta	
Toluene			Toxic waste	
108-88-3			waste number F025	
			Waste description:	
			Condensed light ends, spent	
			filters and filter aids, and	
			spent desiccant wastes from	
			the production of certain	
			chlorinated aliphatic	
			hydrocarbons, by free radical	
			catalyzed processes. These	
			chlorinated aliphatic	
			hydrocarbons are those	
			having carbon chain lengths	
			ranging from one to and	
			including five, with varying	
			amounts and positions of	
			chlorine substitution.	

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Hexane	Toxic
110-54-3	Ignitable
Toluene	Toxic
108-88-3	Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

IATA

<u>UN/ID No</u> UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1

IMDG

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Hexane	Х	Х	Х	Present	Х	Present	Х	Х

Toluene	Х	Х	Х	Present	Х	Present	Х	Х
	, ,	· · ·	, · ·		· · ·		· · ·	1

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Hexane	5000 lb		RQ 5000 lb final RQ
110-54-3			RQ 2270 kg final RQ
Toluene	1000 lb 1 lb		RQ 1000 lb final RQ
108-88-3			RQ 454 kg final RQ RQ 1 lb final
			RQ
			RQ 0.454 kg final RQ

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Hexane - 110-54-3	110-54-3	15-30	1.0
Toluene - 108-88-3	108-88-3	2-12	1.0

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene	1000 lb	X	X	X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65	
Toluene - 108-88-3	Developmental	

U.S. State Right-to-Know Regulations

O.O. State Night-to-Know Regulations				
Chemical Name	New Jersey	Massachusetts	Pennsylvania	
Hexane 110-54-3	Х	X	Х	
Toluene 108-88-3	X	X	X	

16. OTHER INFORMATION

NFPA Health Hazards

Not determined

Health Hazards

Not determined

Flammability
Not determined
Flammability
Not determined

Instability
Not determined
Physical hazards
Not determined

Special Hazards
Not determined
Personal Protection
Not determined

Issue Date:01-Aug-2016Revision Date:01-Aug-2016Revision Note:New format

Disclaimer

<u>HMIS</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet