MATERIAL	SAFE	ΓΥ D	ATA	SH	EE.	T					
OSHA - Meets 29 CFR 1910.1200 Standards	HMIS HAZARD RATINGS										
	FLAMMABILIT	HEALTH10 = INSIGNIFICANFLAMMABILITY11 = SLIGHT			г	T 3 = HIGH 4 = EXTREME					
(<i>6</i> 11/1)/4N/DR®)	REACTIVITY	TRAN	0 ISPORTAT			אר					
TEATHER	PROPER SHIP		Not Regula			511					
LLAIIILI	HAZARD CLAS		Not regulate	ed	REF:	Not Applic					
	IDENTIFICATIO		None		LABEL:	None Req	uired				
SECTION 1 - PRODUCT / COMPANY IDENTIFICATION											
IDENTITY (AS USED ON LABEL AND LIST) PURPLE OIL						F	Page 1 of 2				
MANUFACTURER'S NAME Weaver Leather LLC		EMERGEN 800-25	5-3924								
ADDRESS (NUMBER, STREET, P.O. BOX) 7540 CR 201	TELEPHONE NUMBER FOR INFORMATION 330-674-7548										
(CITY, STATE AND ZIP CODE) Mt. Hope, OH 44660	DATE PREPARED: July 28, 2004 SUPERSEDES: November 25, 2002										
SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION											
HAZARDOUS COMPONENTS	CAS #	%	OSHA			H TWA	SARA	RQ			
(SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))		(OPTIONAL) 100	PPM	MG/M3	PPM	MG/M3	TITLE III	LBS			
Paraffinic petroleum oil Heavy paraffinic petroleum oil	64741-88-4			E (mist)		5 (mist)					
Petroleum distillate, solvent dewaxed heavy paraffinic				5 (mist) 5		5 (IIIISI) 10					
SECTION 3 - HEALTH HAZARD DA	TA										
ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE		EMERGENCY AND FIRST AID PROCEDURES									
INHALATION: High concentrations are irritating to the respiration cause headache, dizziness, nausea, vomiting and malaise.	Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.										
SKIN: Brief contact may cause slight irritation; prolonged cont moderate irritation or dermatitis.	Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.										
EYES: High vapor concentration or contact may cause irritation discomfort.	Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.										
INGESTION: May result in vomiting; aspiration of vomitus into be avoided; DO NOT induce vomiting. Minute amounts aspira can produce severe lung injury, chemical pneumonitis, pulmor death.	DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.										
CARCINOGENICITY	NTP?	No	IARC MON	OGRAPHS?	No	OSHA F	REGULATED?	No			
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EX prolonged exposure.	(POSURE: Preex	isting skin, eye,	or respirator	y disorders	may bec	ome aggrav	vated throug	h			

MATERIAL SAFETY DATA S									
IDENTITY (AS USED ON LABEL AND LIST) PURPLE OIL				Page 2 of 2 Date: July 28, 2004					
SECTION 4 - FIRE FIGHTING MEASURES									
FLASH POINT (METHOD USED) > 265° F (> 129.4° C)		NFPA RATING III B	LEL: Not appl						
EXTINGUISHING MEDIA		IIID							
Carbon dioxide, water fog, dry chemical, chemical foam									
SPECIAL FIRE FIGHTING PROCEDURES									
Firefighters must wear full facepiece self - contained breathing apparatus in positive pressure mode. Do not use solid stream of water since stream will									
scatter and spread fire. Fine water spray can be used to keep fire - exposed containers cool.									
UNUSUAL FIRE AND EXPLOSION HAZARDS									
Closed containers can explode due to buildup of pressure when exposed to extreme heat.									
OFOTION E ADDIDENTAL DELEADE MEADLIDED									
SECTION 5-ACCIDENTAL RELEASE MEASURES									
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WILL SUPPORT COMBUSTION. Do not wash to sanitary sewer. All spills - confine									
spill, soak up with approved absorbent, shovel product into approved container for disposal. Flush area with water, recover flush for proper disposal.									
SECTION & HANDLING AND STOPACE									
SECTION 6 - HANDLING AND STORAGE									
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures onen flames. This material will support computing. Keep this and other chemicals out of reach of children.									
temperatures, open flames. This material will support combustion. Keep this and other chemicals out of reach of children.									
SECTION 7 - EXPOSURE	CONTROLS	PERSONAL P	ROTECTION						
SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA									
exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.									
VENTILATION LOCA	L EXHAUST: Req	uired SPECIA	L: To maintain minimur	m TWA and STEL levels.					
MECHANICAI	GENERAL): Yes	OTHE	R: Engineering and wor	rk controls as required.					
PROTECTIVE GLOVES: Neoprene or rubbe			EYE PROTECTION: Protective eyeglasses or chemical safety goggles.						
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyebath nearby									
WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.									
SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES									
BOILING POINT			C GRAVITY (WATER	1 = 1)					
532° F VAPOR PRESSURE (MM Hg)		0.920 - pH	0.930						
0.1 mm Hg @ 20° C		Not app	licable						
VAPOR DENSITY (AIR = 1)			ATION RATE (n-Buty	/l acetate = 1)					
> 1		< 0.1		,					
SOLUBILITY IN WATER		% VOLAT	TILE (BY WEIGHT)						
Negligible		None							
APPEARANCE AND ODOR									
Purple liquid, sweet pea odor									
SECTION 9 - STABILITY	AND REACTI								
STABILITY	UNSTABLE:		INS TO AVOID: Extreme	e temperatures, open flames					
INCOMPATIBILITY (MATERIALS TO AVOID	STABLE: XXX								
HAZARDOUS DECOMPOSITION OR BYPR	ODUCTS: Decomposi	tion will not occur if handle	d and stored properly. I	n case of a fire, oxides of carbon.					
hydrocarbons, fumes, and smoke may be pro									
HAZARDOUS POLYMERIZATION	MAY OCCUR:	CONDITIC	INS TO AVOID:						
WILI	NOT OCCUR: XXX	None							
SECTION 10 - DISPOSAL CONSIDERATIONS									
WASTE DISPOSAL METHOD: Dispose of in									
a closed disposal container creating a dangerous environment. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal									
regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals. Do not flush to sanitary sewer or waterway.									
			-						
The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current,									
applicable and suited to the circumstances of	use. Vendor assumes	no responsibility for injury	to vendee or third pers	sons proximately caused by the material if					
reasonable safety procedures are not adhered to									
of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.									