68S Renia - corkfiller

Version 5.1 Revision date Jan 28, 2021 Print date Feb 3, 2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

68S Renia - corkfiller

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Adhesives, sealants

1.3 Details of the supplier of the safety data sheet

Supplier

Renia Gesellschaft mbH

Ostmerheimer Straße 516 Telephone: +492216307990 51109 Köln E-mail: info@renia.com Website: www.renia.com

Department responsible for information

E-mail (competent person) labor@renia.com

1.4 Emergency telephone number

Emergency telephone number Grimme: +49-221-630799-17

Only available during office hours.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

- * Flam. Lig. 2; flammable liquids; H225 Highly flammable liquid and vapour.
- * STOT SE 3 Narcotic effects; STOT-single exposure; H336 May cause drowsiness or dizziness.
- * Skin Irrit. 2; Skin corrosion/irritation; H315 Causes skin irritation.
- * Aquatic Chronic 2; Hazardous to the aquatic environment; H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms







Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour. H336 May cause drowsiness or dizziness.

H315 Causes skin irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

* P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing vapours.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

Page 1/8 US (en GB)

68	S	Renia - corkfiller		
Ve	rsion 5.1	Revision date Jan 28, 2021	Print date Feb 3, 2021	
*	P280	Wear protective gloves and eye/face protection.		
	P302 + P352	IF ON SKIN: Wash with plenty of soap and water.		
	P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing shower].	g. Rinse skin with water [or	
	P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for	breathing.	
	P312	Call a POISON CENTER if you feel unwell.	9	
	P332 + P313	If skin irritation occurs: Get medical advice/attention.		
	P362 + P364	Take off contaminated clothing and wash it before reuse.		
	P370 + P378	In case of fire: Use extinguishing powder or sand to extinguish.		
	P391	Collect spillage.		
	P403 + P233	Store in a well-ventilated place. Keep container tightly closed.		
	P403 + P235	Store in a well-ventilated place. Keep cool.		
	P405	Store locked up.		
	P501	Dispose of contents/container to industrial incineration plant.		
	Hazard components for	or lahelling		

Hazard components for labelling

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

No information available.

SECTION 3: Composition / information on ingredients

3.2 Mixtures

Description

natural rubber with modified synthetic resins and stabilizers in a mixture of organic solvents.

Hazardous ingredients

CAS No. EC No. INDEX No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
921-024-6 649-328-00-1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 01-2119475514-35 Flam. Liq. 2 H225 / Asp. Tox. 1 H304 / Skin Irrit. 2 H315 / STOT SE 3 H336 / Aquatic Chronic 2 H411	75,0 < 80,0

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

not applicable

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

US (en_GB) Page 2/8

68S Renia - corkfiller

Version 5.1 Revision date Jan 28, 2021 Print date Feb 3, 2021

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

No special measures are necessary.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. Personal protection equipment: see section 8 Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Store in a well-ventilated and dry room at temperatures between 10 °C and 30 °C.

7.3 Specific end use(s)

Page 3/8 US (en GB)

68S Renia - corkfiller

Version 5.1 Revision date Jan 28, 2021 Print date Feb 3, 2021

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No data available

Biological limit values

No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
-	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term dermal (systemic)	773 mg/kg
-	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term inhalative (systemic)	2.035 mg/m³

DNEL Consumer

CAS No.	Substance name	DNEL type	DNEL value
-	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term dermal (systemic)	699 mg/kg
-	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term inhalative (systemic)	608 mg/m³
-	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term oral (repeated)	699 mg/kg

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber)

* Thickness of the glove material: >= 0.4 mm

Breakthrough time (maximum wearing time): >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection

Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state liquid
Colour light yellow

Page 4/8 US (en GB)

68S Renia - corkfiller

Version 5.1 Revision date Jan 28, 2021 Print date Feb 3, 2021

Safety characteristics

Odour characteristic
Odour threshold not determined

pH at 20 °C: not determined

Melting point/freezing point -20 °C
Initial boiling point and boiling range > 65 °C
Flash point -25 °C

Evaporation rate at 20°C not determined Burning time (s) not relevant Lower explosion limit at 20°C 1 Vol-% Upper explosion limit at 20°C 7.3 Vol-% Vapour pressure at 20°C 175 mbar Density at 20°C 0,743 kg/l Water solubility (g/L) at 20°C not determined Partition coefficient: n-octanol/water see section 12

* Ignition temperature in °C 258 °C

Decomposition temperature not determined

Viscosity 20.000 mPas
Explosive properties not relevant
Oxidising properties not relevant

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

LD50: (Rat): > 5.000 mg/kg; (OECD 401) LC50: (Rat): > 20 mg/l (4 h); (OECD 403)

Page 5/8 US (en GB)

68S Renia - corkfiller

Version 5.1 Revision date Jan 28, 2021 Print date Feb 3, 2021

LD50: dermal (Rabbit): > 2.000 mg/kg; (OECD 402)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Acute (short-term) fish toxicity

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 11.4 mg/l (96 h)

Acute (short-term) toxicity to aquatic algae and cyanobacteria

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

EL50: (Pseudokirchneriella subcapitata): = 30 < x > 100 mg/l (72 h)

Acute (short-term) toxicity to crustacea

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

EL50: (Daphnia magna (Big water flea)): = 3 mg/l (48 h)

12.2 Persistence and degradability

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Biodegradation; (Activated sludge) = 81 % (28 d)

Method: OECD 301F/ ISO 9408/ EEC 92/69/V. C.4-D

Readily biodegradable (according to OECD criteria).

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Page 6/8 US (en GB)

68S Renia - corkfiller

Version 5.1 Revision date Jan 28, 2021 Print date Feb 3, 2021

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

* 080409* - Waste adhesives and sealants containing organic solvents or other dangerous substances

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number

UN 1133

14.2 UN proper shipping name

Land transport (ADR/RID)

KLEBSTOFFE (enthält Kohlenwasserstoffe, C6-C7, Isoalkane, Cyclene, <5% n-Hexan)

Sea transport (IMDG)

Adhesives (contain Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane)

Air transport (ICAO-TI / IATA-DGR)

Adhesives (contain Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane)

14.3 Transport hazard class(es)

Land transport (ADR/RID) 3
Sea transport (IMDG) 3
Air transport (ICAO-TI / IATA-DGR) 3

14.4 Packing group

Land transport (ADR/RID)

for packages < = 450 litres: III

Sea transport (IMDG)

for packages < 30 litres: III

Air transport (ICAO-TI / IATA-DGR)

for packages < 30 litres:III

14.5 Environmental hazards

Land transport (ADR/RID) ENVIRONMENTALLY HAZARDOUS

Sea transport (IMDG) Marine pollutant / Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

tunnel restriction code: D/E for packages < = 450 litres: E

Special provisions SV 640C

Sea transport (IMDG)

* EmS-Code: F-E, S-D

Air transport (ICAO-TI / IATA-DGR)

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Page 7/8 US (en GB)

68S Renia - corkfiller

Version 5.1 Revision date Jan 28, 2021 Print date Feb 3, 2021

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 580,956 g/l

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

E2 Hazardous to the aquatic environment in Category Chronic 2

Quantity 1: 200t; Quantity 2: 500t

P5c Flammable liquids

Quantity 1: 5.000t; Quantity 2: 50.000t

National regulations

15.2 Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

REACH No. Substance name

01-2119475514-35 Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

SECTION 16: Other information

Relevant R-, H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2 On basis of test data. STOT SE 3 Narcotic Calculation method.

effects

Skin Irrit. 2 Calculation method.
Aquatic Chronic 2 Calculation method.

Abbreviations and acronyms

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

Indication of changes

Page 8/8 US (en GB)

^{*} Data changed compared with the previous version